

## LubiQ C4 V 5W-30 Low SAPS Engine Oil Technical Data Sheet – L4738

LubiQ C4 R 5W-30 is a high quality, fully synthetic motor oil featuring low SAPS technology, formulated for use in both petrol and diesel engines. It has been formulated to meet the requirements of high-performance passenger car engines, including those requiring ACEA C4.

This engine exhibits exceptional durability and anti-wear long life performance, as well as delivering excellent control of sludge, soot, and piston deposits. It has excellent oxidation stability and offers protection against rust and corrosion with the low SAPS formulation ensuring protection of exhaust after-treatment systems.

This oil is recommended for use in passenger cars and light commercial vehicles, those fitted with exhaust after-treatment systems, where the original equipment manufacturer recommends an engine lubricant of this quality, viscosity, and performance level.

### Performance Features:

- Low-SAPS emission compatible technology
- Exceptional protection against engine wear
- Control over sludge, soot, and piston deposits
- Excellent thermal and oxidation stability
- Low evaporative loss formulation
- Exceptional shear stability
- Protects against rust and corrosion
- Excellent cold flow characteristics

### Typical Data:

Density @ 15.6°C	kg/l	0.847	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	67.2	ASTM D445
Kinematic Viscosity @ 100°C	cSt	11.7	ASTM D445
Viscosity Index		171	ASTM D2270
Flashpoint (Open)	°C	230	ASTM D92
Pour Point	°C	-39	ASTM D97
CCS @ -30°C	mPa.s	6130	ASTM D5293
Total Base Number	mg KOH/g		ASTM D2896

Figures based on average production values.

### Performance Levels:

ACEA C4 (2016)  
Renault RN 0720  
Mercedes 226.51

Issue 1 December 2020 The above information is supplied to the best of our knowledge and belief based on current industry and our own development work. Subject to amendment.