



LubiQ C3 V 5W-30 Synthetic Engine Oil – L4736

LubiQ C3 V 5W-30 is a high quality, fully synthetic motor oil featuring emissions compatible technology, which enables exhaust after-treatment systems to remain clean and maintain engine performance.

The high-quality synthetic formulation promotes exceptional long term anti-wear performance and oxidation stability, as well as delivering excellent high and low temperature performance.

The product exhibits outstanding control over soot, sludge and deposits delivering very high standards of engine cleanliness. The product offers excellent resistance to evaporation loss and displays high shear stability.

Applications

LubiQ C3 V 5W-30 has been primarily formulated for use in Volkswagen Group vehicles but is also suitable for use in other vehicles where the original equipment manufacturer recommends a lubricant of this quality, viscosity and performance level.

Performance Features

- Mid-SAPS emission compatible technology
- Protects against engine wear
- Control over sludge and piston deposits
- Excellent thermal and oxidation stability
- Low evaporation formulation Maintains viscosity
- Protects against rust and corrosion
- Excellent cold flow characteristics

Typical Data

Characteristic	Unit	Result	Method
Density @ 15.6°C	kg/l	0.849	ASTM D4052
Kinematic Viscosity @ 40°C	cSt	71.1	ASTM D445
Kinematic Viscosity @ 100°C	cSt	11.9	ASTM D445
Viscosity Index		164	ASTM D2270
Flashpoint (Open)	°C	220	ASTM D92
Pour Point	°C	-39	ASTM D97
CCS @-30°C	mPa.s	6070	ASTM D5293
Total Base Number	mg KOH/g	8.7	ASTM D2896

Figures based on average production values

Performance Levels:

- ACEA C3 (2016)
- VW 504.00/507.00
- MB 229.51
- BMW LL-04
- Porsche C30

Issue 1 December 2020 The above information is supplied to the best of our knowledge and belief on the basis of current industry and our own development work. Subject to amendment.